



SIGN	DESCRIPTION	DATE	APPROVER

Technical Data:

Material:

Terminal: Copper Alloy, Tin plated.
Wire guard: Copper Alloy,
Insulator body(housing): Polyamide(UL94V-0)

Electrical:

Voltage rating: 300VAC
Current rating: 20 Amps/way max
Contact resistance: 20mΩ (max)
Withstanding Voltage: 2500VAC(1min) Test time=60sec/1pcs
Wire range: 12-26AWG

Mechanical:

Operating temperature: -40°C to +120°C
Soldering reliability:
Test temperature= 250°C±10°C
5 seconds max

Ordering Information:

F75-I- G XX-0 0 X X 0 000

- | | | | |
|----|----------------|---|--------|
| 2 | 02 | 1 | Brown |
| - | - | 2 | Red |
| 24 | 24 | 3 | Orange |
| | | 4 | Yellow |
| | | 5 | Green |
| | | 6 | Blue |
| | | 7 | Purple |
| | | 8 | Gray |
| 0 | Without Flange | 9 | White |
| 1 | With Flange | A | Black |

WELINK 上海拓尔普电子科技有限公司
Welink International Co., LTD.

TOLERANCE X. ±0.50 X.X ±0.30 X.XX ±0.20 X° ±1°	APPROVED:	NAME: F75-I -Pitch 7.62mm -Series	
	CHECKED:		
	DRAWN: Ling Yu 2012,03,10		
	UNITS: mm REV: A	PART NO: F75IGXX001X0000	
	SCALE: 2.5 / 1	PAGE: 1 / 1	DWG NO: 9F75IG001A