



N=Number of contacts

SIGN	DESCRIPTION	DATE	APPROVER

Technical Data:

Material:

Contact(metal housing): Copper Alloy with Ni plated
 Terminal screw: Steel galvanized with Cr3+ plated
 Wire guard: Copper Alloy, Tin plated.
 Insulator body(housing): Polyamide(UL94V-0)

Electrical

Voltage rating: 300VAC
 Current rating: 12 Amps/way max
 Contact resistance: 20mΩ(max)
 Withstanding Voltage: 2500VAC(1min) Test time=60sec/1pcs
 Wire range: 14-26AWG

Mechanical:

Torque: 4.0kgf.cm/M2.5
 Operating temperature: -40°C to +105°C
 Soldering reliability:
 Test temperature= 250°C±10°C
 5 seconds max

Ordering Information:

F73-2-E XX-X 0 XX 0-0 0 0

- | | | | | |
|----|------------|---------|---|----------------|
| 2 | 02 | └──┬──┘ | 5 | Green |
| - | - | | 6 | Blue |
| 24 | 24 | └──┬──┘ | 8 | Grey |
| | | | 9 | White |
| | | | A | Black |
| | | | 1 | With flange |
| 1 | "-" SCREW | └──┬──┘ | 2 | Without flange |
| 2 | "-/" SCREW | | | |

WELINK 上海拓尔普电子科技有限公司
 Welink International Co., LTD.

TOLERANCE X. ±0.50 X.X ±0.30 X.XX ±0.20 X° ±1°	APPROVED:	NAME: F73-2 Pitch 5.08mm -seriec Without flange
	CHECKED:	
	DRAWN: Ling Yu 2016.12.12	
	UNITS: mm	REV: A
	SCALE: 4 / 1	PAGE: 1 / 1
		PART NO: F732EXX102X0000
		DWG NO: 9F732E001A